

Data sheet

Commercial Art.No.: R1.188.4000.0

Device for monitoring of safety-related circuits SNO4003K-C 115-120 VAC

Basic device, Single-channel control in supply circuit, automatic / manual reset with reset button monitoring, 3 NO contacts, 1 NC contact, AC 115-120 V 50-60Hz, push-in terminals pluggable



Commercial Art.No.	R1.188.4000.0
EAN	4049088206856
Order Unit	1

Certificates / Approvals



Technical data

General

Function display	2 LED, green
Creepage distances and clearances between the circuits	EN 60664-1
Protection degree according to DIN EN 60529 (housing)	IP40
Protection degree according to DIN EN 60529 (terminals)	IP20
Ambient temperature min.	-25 °C
Ambient temperature max.	55 °C
Wire range cage clamp terminals	2 x 0,25mm ² - 1,5mm ²
Weight	0.25 kg
Standards	EN ISO 13849-1EN 62061; EN 62061
Suited for safety functions	Yes
With muting function	No
Feedback circuit	Yes
Start contact	Yes
Stop category acc. to IEC 60204	0
Rail mounting possible	Yes

Connection Data

Detachable clamps	Yes
Type of electric connection	Tension clamp connection

Application

Model	Basic device
Suitable for monitoring of magnetic switches	No
Suitable for monitoring of proximity switches	Yes
Suitable for monitoring of emergency-stop circuits	Yes
Suitable for monitoring of optoelectronic protection equipment	No
Suitable for monitoring of position switches	Yes

Output circuit

Enabling paths	Normally open contact
----------------	-----------------------

Signaling paths	Opener
Contact material	Ag-alloy, gold-plated
Rated switching voltage, enabling paths AC	230 V
Rated switching voltage, enabling paths DC	24 V
Rated switching voltage, signaling paths AC	230 V
Rated switching voltage, signaling paths DC	24 V
Max. thermal current I _{th} , enabling paths	8 A
Max. thermal current I _{th} , signaling paths	5 A
Max. total current I ² of all current path	9 A ²
Application category AC-15 (NO)	Ue 230V, Ie 5A
Application category DC-13 (NO)	Ue 24V, Ie 5A
Short-circuit protection (NO), max. fuse insert	6 A class gG fuse, fuse integral < 100 A ² s
Mechanical life	107 switching cycles
Outputs, signalling function, undelayed, with contact	1
Outputs, safe, undelayed, with contact	3

Control circuit

Nominal output voltage DC	24 V
Input current (safety circuit / reset circuit)	90 mA
max. peak current (safety circuit / reset circuit)	1500 mA
Response time t _{A1}	60 ms
Response time t _{A2}	180 ms
Min. switch-on time	60 ms
Recovery time t _W	> 200 ms
Release time t _R	< 80 ms
max. resistivity, per channel	≤ (7,5 + (1,176 x U _B / U _N - 1) x 150) Ω
Type of switch function of the inputs	Normally open contact
Evaluation inputs	1-channel

Supply circuit

Nominal voltage U _N	AC 115-120 V
Rated consumption AC	2.3 VA
Rated frequency min.	50 Hz
Rated frequency max.	60 Hz
Operating voltage min.	97.8 V
Operating voltage max.	132 V
Electrical isolation supply circuit - control circuit	Yes
Min. rated control supply voltage at AC 50 Hz	97.8 V
Max. rated AC voltage for controls, 50 Hz	132 V
Rated control supply voltage at AC 60HZ	97.8 V
Rated control supply voltage at AC 50HZ	132 V

Dimensions

Depth	114 mm
Width	22.5 mm
Height	106.5 mm

Classification

ECLASS 8.1	27371819
ETIM 7.0	EC001449
ETIM 6.0	EC001449
ETIM 5.0	EC001449
ETIM 4.0	EC001449
ETIM 3.0	EC001449




Safety parameters

Category (ISO 13849-1)	4
------------------------	---

PL (ISO 13849-1)	Level e
SILCL (IEC 62061)	3
PFDD (Low demand mode)	3.6 E-6
PFHD (High demand mode)	8.6 E-10 1/h
HFT	1
SSF	99.5 %
DC	99 %
MTTFd	73 a
λ S	1570 FIT
λ D	1570 FIT
λ DU	1554 FIT
λ DD	16 FIT
TM	20 a
Proof test intervall (High demand mode)	20 a
Proof test intervall (Low demand mode)	1 a

Teile Nr. / Part No.
R1.188.1940.0
R1.188.1950.0
R1.188.1960.0
R1.188.1970.0
R1.188.1980.0
R1.188.1990.0
R1.188.2000.0
R1.188.2010.0
R1.188.2020.0
R1.188.2390.0
R1.188.2410.0
R1.188.2420.0
R1.188.2430.0
R1.188.2440.0
R1.188.2450.0
R1.188.3400.0
R1.188.3410.0
R1.188.3420.0
R1.188.3430.0
R1.188.3490.0

Teile Nr. / Part No.
R1.188.3600.0
R1.188.3610.0
R1.188.3630.0
R1.188.3650.0
R1.188.3670.0
R1.188.3730.0
R1.188.3820.0
R1.188.3850.0
R1.188.3860.0
R1.188.3900.0
R1.188.3920.0
R1.188.3940.0
R1.188.4000.0
R1.188.4010.0
R1.188.4030.0
R1.188.4130.0
R1.188.4140.0
R1.188.4150.0
R1.188.4160.0
R1.188.4210.0



Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited.

©

Weitere Angaben siehe KATALOG oder eKatalog. Additional data see CATALOG or eCatalog. www.wieland-electric.com eshop.wieland-electric.com

ja/yes <input type="checkbox"/> Stoffverbots- und Deklarationsliste nach WN 5020.010 ist einzuhalten. Conformity with Wieland document WN 5020.010 e (list of prohibited / declarable hazardous substances) to be declared!		1. Verwendung: First Use:		Blatt: Sheet:	
Freitoleranz nach General tolerance		CAD-Zeichnung, keine manuellen Änderungen CAD-Drawing, no manual modifications allowed		Zeichnung Nr./Drawing No. T R1.188.1940.0 01K	
Werkstoff/Material		2014 gezeichnet drawn	Tag/Date 06.06.	Name Kötzner	
③	26.08.16	Maßstab/Scale		Maße in mm/Dimensions are in mm	
④	22.04.16				
⑤	03.07.15	Datei/File: 036141_E01K.DCD	Ersatz für/Replacement for:		
⑥	30.06.15		Type	Benennung/Title Maßbildzeichnung/Dimension drawing Standardgehäuse u. -deckel, Baubreite 22,5mm, Federkraftklemme steckbar	
⑦	03.02.15			Standard housing and cover, overall width 22,5mm plug-in spring-clamp terminal	
Index	Datum/Blatt Date/Sheet	wieland www.wieland-electric.com			
Änderung/Revision					

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
M1
M2
M3
L
G
i
11.1
12.1
1.1