
Electrical Noise


LPMS-10A-08 Super Miniature Slip Ring

The LPMS-10A-08 super miniature slip ring is a standard, off-the-shelf unit that uses gold contacts at the rotary interface. And the housing material is engineering plastic or metal. Color-coded lead wires are used on both the stator and rotor for simplifying electrical connections.

The LPMS-10A-08 allows tremendous flexibility in dea system size restrictions. It is available in 1-8 circuit configuration

		LPMS-10A-08 /		
aling	with			
ions.				







TEMPERATURE RANGE -20° C to 60° C

Applications

- **Electrical test equipment**
- Manufacturing and process control equipment
- ✓ Indexing tables
- **CTV** pan / tilt camera mounts
- **Robotics**, rotary sensors, urgent illumination equipmen
- **Exhibit** / display equipment
- Min-type wire-rolling machine
- Closed-circuit control

Specifications				
Operating Speed	0-300 rpm			
Number of Circuits	8			
Voltage	240 VAC/DC			
Current Rating	1amp per circuit			
Temperature Range	-20°℃ to +60°℃			
Contact Material	Gold to Gold			
Wire Size	30# silver plated copper			
Wire Length	Standard 250 mm (9.843inch)			
Dielectric Strength	≥500 VAC @50Hz, between each circuit			
Insulation Resistance	1000 MΩ @ 500 VDC			

Capsule Length					
# of Circuits	L (mm)	Part No			
8	14.6	LPMS-10A-08			

1mΩ Min



- **8** circuits models
- **☑** 1 amp per circuit, 240 VAC/DC
- **V** Precision assembly to provide exceptional rotational life
- Speed up to 300 rpm continuous
- Gold to Gold contacts

Flexible, color-coded, silver-plated lead wires

- Superior handling of low level control signals
- **Precious metals contacts**



MAXIMUM OPERATING SPEED 0-300 RPM



www.slipring.cn

Advantage



- **V** Low torque minimizes system torque budget
- Compatible with all kinds of data signals
- Smooth running, compact design
- **Extremely small and stable electric noise**
- Compact design to fit in the most demanding space
- **360° continuous rotation**
- **W** High bandwidth transfer capability
- **Addition of special components**
- Gold to gold contacts, excellent digital transmission performance and high working life


HNPAT

Compact package

Wre Color Code								
Wire Size	Ring #	Color	Ring #	Color	Ring #	Color	Ring #	Color
30# Silver Plated Copper	#1	BLK	#2	BRN	#3	RED	#4	ORG
	#5	YEL	#6	GRN	#7	BLK-BLU	#8	PUR
	#9	GRAY	#10	WIT	#11	PINK	#12	AZURY
	#13	WIT/BLK	#14	WIT/BRN	#15	WIT/RED	#16	WIT/ORG
	#17	WIT/YET	#18	WIT/GRN	#19	WIT/BLU	#20	WIT/PUR
	#21	WIT/GRAY	#22	CLAR	#23	BLK-RED	#24	BLK/BRN

Remarks: 1. AWG30# silver plated copper Teflon UL, 24 different color single wires for a circle

2. #1 from rotor side (The color if the wire can be changed).



Drawings

Any questions about slip ring, please leave your message to get a professional solution

RODUC		

FORJ Capsule slip ring Through bore slip ring Pancake slip ring Mercury slip ring Separate slip ring Miniature slip ring Wind turbine slip ring Hydraulic slip ring Pneumatic slip ring Coaxial rotary joints

Circuits Dimension Operating Environment Other



+1 346-320-9106

Stator Side 1st Ring Ø10 Stator Lead Wires 14.6

MESSAGE

- Current&voltage
- Signal details
- Working speed
- Working temperature

Surveillance Crane **Medical** Marine Defence Radar antenna **Automation** Meter and instrument Wind turbine generator **VR** Device Other

